

NEUTRIK NAC3FXXB-W-S

NAC3FXXB-W-S

IEC EN 60320-1 compliant | Accepted for cord sets as per IEC EN 60799:2021

Locking AC mains cable connector, keyed and color coded (grey) for power-out, screw terminal assembly, for cable diameters 6 - 12 mm.

The powerCON FXXA/FXXB is a single phase (3 conductor) lockable power connector with Circuit Breaking Capability when mated with powerCON XX Series receptacles.

It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed to guarantee a safe power connection.

[NAC3FXXB-W-S connector - three views — 1. oldal](#)

Features & Benefits

- IEC EN 60320-1 / UL 60320-1 / CSA C22.2 No. 60320-1 certified, thus accepted as a component for cord sets acc. to IEC 60799 / UL 817 and equipment acc. to IEC 62368-1 UL US 498 / UL CA 498
- Ergonomic design with slip-proof two-component molded housing
- Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating
- Unique NEUTRIK locking bushing and strain relief for cable diameters 6 mm to 12 mm
- Easy to assemble because the strain relief locks with the insert mechanically and aligns with the housing
- Superior NEUTRIK quality standard, extremely robust and reliable
- Easy and reliable twist lock system
- Improved kink protection by two-component bushing

Cable list

Cable: IEC/EN 60320-1	3 x 1.5 mm²	3 x 2.5 mm²
-----------------------	-------------	-------------

■ H07RN-F	-S	-L
■ H05RN-F	-S	-
■ H05VV-F	-S	-S

Cable: UL 60320-1, CAN/CSA-C22.2 No. 60320-1	16/3 AWG	14/3 AWG	12/3 AWG
■ SOOW	-S	-L	-L
■ SJOOW	-S	-S	-L
■ SJTOOW	-S	-S	-S

Technical Information

Product

Title	NAC3FXXB-W-S
Connector series	powerCON blue/grey

Electrical

Contact resistance	≤ 2 mΩ
Dielectric strength	> 3 kVac (after mating cycles)
Insulation resistance	> 10 GΩ (initially)
Number of electrical contacts	2 + PE
Rating Europe	EN 60320-1: 16 A 250 V AC, CBC
Rating USA / Canada	cUL 60320-1: 20 A 127 V AC UL USA 498: 20 A 127 V AC UL CA 498: 20 A 127 V AC

Mechanical

Cable O.D.	6 - 12 mm
Lifetime	> 5'000 mating cycles
Wiresize (mm²)	1.5 – 2.5 mm²

Cable O.D.	6 - 12 mm
Wiresize (AWG)	16 - 12 AWG, see above cable list
Locking device	Twist lock
Termination	Screw type terminals

Material

Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

Environmental

Temperature range	-33 °C to + 80 °C
Protection class	IP20
Flammability acc. to UL94	V-0

NAC3FXXB-W-S | All rights reserved / 11.09.2026 | 4/4

Eredeti dokumentumok

- [nac3fxxb-w-s.pdf](#)

<https://invgroup.hu/product/nac3fxxb-w-s/>